

**ACT8GER72E4H667S**  
8GB DDR2-667 Registered ECC DIMM

**Description**

ACTICA ACT8GER72E4H667S is a high speed 8GB DDR2-667 2 ranks Registered ECC DIMM . It is designed for mission critical application memory solution. This DIMM includes Error Checking and Correcting (ECC) for maximum reliability. The modules is constructed using 2Gbit SDRAMs, and is fully compliant with JEDEC specifications. Decoupling capacitors are mounted on the PCB board for better signal integrity. The DIMM feature serial presence detect (SPD) based on a serial EEPROM device using the 2-pin I2C protocol.

Features	Value
ACTICA memory P/N	ACT8GER72E4H667S
CL-tRCD-tRP	5-5-5
ECC	Yes
RoHS compliant	Yes
Supply Voltage	1.8V ± 0.1V
JEDEC standard	Yes
Operating Temperature*	0 - 95 °C
<b>Timing Parameter:</b>	
tCK (Clock Cycle Time)	3ns
tRCD (Ras and Cas Delay)	15ns
tRP (Row Precharge Time)	15ns
tRAS (Row Active Time)	45ns
tIH (Input Hold Time)	275ps
tIS (Input Setup Time)	200ps
<b>Operating Current:</b>	
IDD0 (Operating one bank active-precharge current)	3,500 mA
IDD1 (Operating one bank active-read-precharge current)	3,800 mA
IDD2P (Precharge power-down current)	1,600 mA
IDD3N (Active standby current)	3,000 mA
IDD6 (Self refresh current)	800 mA

\* At 85 - 95 °C operation temperature range, doubling refresh commands in frequency to a 32ms period ( tREFI=3.9 us ) is required, and to enter to self refresh mode at this temperature range, an EMRS command is required to change internal refresh rate.

**Physical Dimension** (drawing not in scale) Units : in Millimeters

