

ACT1GEU72T8F800S
1GB DDR2-800 Unbuffered ECC DIMM

Description

ACTICA ACT1GEU72T8F800S is a high speed 1GB DDR2-800 Unbuffered ECC DIMM . It is designed for mission critical application memory solution. This DIMM includes Error Checking and Correcting (ECC) for maximum reliability. The modules is constructed using Samsung SDRAMs, and is fully compliant with JEDEC specifications. Decoupling capacitors are mounted on the PCB board for better signal integrity. The DIMM feature serial presence detect (SPD) based on a serial EEPROM device using the 2-pin I2C protocol.

Features	Value
ACTICA memory P/N	ACT1GEU72T8F800S
CL-tRCD-tRP	5-5-5
ECC	Yes
RoHS compliant	Yes
Supply Voltage	1.8V ± 0.1V
JEDEC standard	Yes
Operating Temperature*	0 - 95 °C
Timing Parameter:	
tCK (Clock Cycle Time)	2.5ns
tRCD (Ras and Cas Delay)	12.5ns
tRP (Row Precharge Time)	12.5ns
tRAS (Row Active Time)	45ns
tIH (Input Hold Time)	250ps
tIS (Input Setup Time)	175ps
Operating Current:	
IDD0 (Operating one bank active-precharge current)	1,120 mA
IDD1 (Operating one bank active-read-precharge current)	1,210 mA
IDD2P (Precharge power-down current)	140 mA
IDD3N (Active standby current)	900 mA
IDD6 (Self refresh current)	140 mA

* At 85 - 95 °C operation temperature range, doubling refresh commands in frequency to a 32ms period (tREFI=3.9 us) is required, and to enter to self refresh mode at this temperature range, an EMRS command is required to change internal refresh rate.

Physical Dimension (drawing not in scale) Units : in Millimeters

