

**ACT1GHU72C8G1333S**  
**1GB DDR3-1333 Unbuffered ECC DIMM**
**Description**

ACTICA ACT1GHU72C8G1333S is a high speed 1GB DDR3-1333 Unbuffered ECC DIMM. It is designed for mission critical application memory solution. The module is fully compliant with JEDEC specifications. Decoupling capacitors are mounted on the PCB board for better signal integrity. The DIMM feature serial presence detect (SPD) based on a serial EEPROM device using the 2-pin I2C protocol.

Features	Value
ACTICA memory P/N	ACT1GHU72C8G1333S
CL-tRCD-tRP	9-9-9
RoHS compliant	Yes
Supply Voltage	1.5V ± 0.075V
JEDEC standard	Yes
Operating Temperature*	0 - 95 °C
<b>Timing Parameter:</b>	
tCK (Clock Cycle Time)	1.5ns
tRCD (Ras and Cas Delay)	13.5ns
tRP (Row Precharge Time)	13.5ns
tRAS (Row Active Time)	36ns
tIH (Input Hold Time)	140ps
tIS (Input Setup Time)	65ps
<b>Operating Current:</b>	
IDD0 (Operating one bank active-precharge current)	810 mA
IDD1 (Operating one bank active-read-precharge current)	980 mA
IDD2P (Precharge power-down current)	100 mA
IDD3N (Active standby current)	580 mA
IDD6 (Self refresh current)	85 mA

\* At 85 - 95 °C operation temperature range, doubling refresh commands in frequency to a 32ms period ( tREFI=3.9 us ) is required, and to enter to self refresh mode at this temperature range, an EMRS command is required to change internal refresh rate.

**Physical Dimension** (drawing not in scale) Units : in Millimeters
